

# Jandy® Watermatic Automated Liquid Chlorine Feeder Systems

*Affordable automation for commercial  
and residential pools, spas  
and water features*

The Jandy Watermatic L-1 and L-2 are complete systems for feeding liquid chlorine and liquid muriatic acid. Easy to install, operate and maintain, both systems include controllers that plug into any 120V outlet and control two peristaltic pumps. The L-2 System provides adjustable-rate pumps.



### Benefits

- Complete liquid system
- Easy to install and maintain
- Clean, clear water 24 hours a day, seven days a week
- Toll-free technical assistance

### Included In L-1 System

- C2000 ORP / pH controller with flow cell
- 3-310 Peristaltic pump (2)
- 9-960 Mounting board

### Included In L-2 System

- C2000 ORP / pH controller with flow cell
- 3-313 Adjustable-rate peristaltic pump (2)
- 9-960 Mounting board



2620 Commerce Way, Vista, CA 92081-8438  
760-599-9600 • 1-800-822-7933  
[www.jandy.com](http://www.jandy.com)

# Jandy® Watermatic L-1 and L-2

## L-1 Specifications

### CONTROLLER

ORP Control: 200 to 900 mV  
pH Control: 7.0-8.0  
ORP Sensors: Gold-tipped w/ 10' cable  
Readout: Graphic LCD, menu driven  
Feed Rate: Adjustable  
Electrical Input: 120/240 VAC  
Electrical Output: 120/240 VAC  
Output Rating: 8 Amps @ 120V 4 Amps @ 240V  
Max load 120V 6.4A, 240V 3.2A  
Alarm: Optional external alarm  
Enclosure: 8" x 9.75" x 5.25"

## L-2 Specifications

### CONTROLLER

ORP Control: 200 to 900 mV  
pH Control: 7.0-8.0  
ORP Sensors: Gold-tipped w/10' cable  
Readout: Graphic LCD, menu driven  
Feed Rate: Adjustable  
Electrical Input: 120/240 VAC  
Electrical Output: 120/240 VAC  
Output Rating: 8 Amps @ 120V 4 Amps @ 240V  
Max load 120V 6.4A, 240V 3.2A  
Alarm: Optional external alarm  
Enclosure: 8" x 9.75" x 5.25"

## Peristaltic Pump

Power: 120 VAC 60 cyl standard  
Output rating: 1.7  
Maximum output: 50 gal/day @ 25 psi  
Dimensions: 8"L x 5.25"H x 4.5"D

## Peristaltic Pump

Power: 120V 60 cyl standard  
Output rating: 1.7  
Maximum output: 50 gal/day @ 100 psi  
Dimensions: 10.6"L x 5.3"H x 6.0"D

## Typical Installation

